



GU10 - NON DIMMABLE (240V)



25,000 Hours



3 Years Warranty



DOM001
DOM002
DOM003



DOM004
DOM005
DOM006



DOM007
DOM008
DOM009



BENEFITS


- Eco Friendly, perfect replacement for general lighting.
- Compatible with all luminaires, easy to install and operate.
- Extra long lifetime, reduces hassle of frequent replacements.

ADVANTAGES

- Excellent optical design, consistency in colour of light.
- Reliable IC solution, automatic production.
- S-shaped base, IEC standard size.

APPLICATIONS

- Market, Walkways, Hospital, Shops & Domestic.



PART NO.	WATTAGE	REPLACEMENT WATTAGE	LUMENS	CCT (K)	CRI (Ra)	POWER FACTOR	BASE	MAX DIMENSIONS (mm)	
								Diameter	Length
DOM001	3.6W	35	250	3000	80	>0.5	GU10	50	54
DOM002	3.6W	35	255	4000	80	>0.5	GU10	50	54
DOM003	3.6W	35	260	6500	80	>0.5	GU10	50	54
DOM004	5W	50	350	3000	80	>0.5	GU10	50	54
DOM005	5W	50	370	4000	80	>0.5	GU10	50	54
DOM006	5W	50	370	6500	80	>0.5	GU10	50	54
DOM007	5.8W	60	425	3000	80	>0.5	GU10	50	54
DOM008	5.8W	60	430	4000	80	>0.5	GU10	50	54
DOM009	5.8W	60	440	6500	80	>0.5	GU10	50	54

BOX QUANTITY = 20

GU10 RETRO - NON DIMMABLE (240V)



25,000 Hours



3 Years Warranty



DOM010
DOM011
DOM012



DOM013
DOM014
DOM015



BENEFITS


- Ideal replacement for traditional halogen lamp.
- Attractive appearance, featuring a retro design.
- Extra long lifetime.

ADVANTAGES

- Professional lens design, perfect quality of light.
- Reliable IC solutions
- S-shaped base, IEC standard size.

APPLICATIONS

- Market, Walkways, Hospital, Shops & Domestic.



PART NO.	WATTAGE	REPLACEMENT WATTAGE	LUMENS	CCT (K)	CRI (Ra)	POWER FACTOR	BASE	MAX DIMENSIONS (mm)	
								Diameter	Length
DOM010	3.6W	35	250	3000	80	>0.4	GU10	50	54
DOM011	3.6W	35	255	4000	80	>0.4	GU10	50	54
DOM012	3.6W	35	255	6500	80	>0.4	GU10	50	54
DOM013	4.4W	50	345	3000	80	>0.4	GU10	50	54
DOM014	4.4W	50	360	4000	80	>0.4	GU10	50	54
DOM015	4.4W	50	360	6500	80	>0.4	GU10	50	54

BOX QUANTITY = 20

GU10 - DIMMABLE (240V)



PART NO.	WATTAGE	REPLACEMENT WATTAGE	LUMENS	CCT (K)	CRI (Ra)	POWER FACTOR	BASE	MAX DIMENSIONS (mm)	
								Diameter	Length
DOM020	4W	35	250	3000	80	>0.5	GU10	50	54
DOM021	4W	35	260	4000	80	>0.5	GU10	50	54
DOM022	4W	35	270	6500	80	>0.5	GU10	50	54
DOM023	5W	50	345	3000	80	>0.5	GU10	50	54
DOM024	5W	50	350	4000	80	>0.5	GU10	50	54
DOM025	5W	50	370	6500	80	>0.5	GU10	50	54
DOM026	6W	60	440	3000	80	>0.5	GU10	50	54
DOM027	6W	60	470	4000	80	>0.5	GU10	50	54
DOM028	6W	60	480	6500	80	>0.5	GU10	50	54

BOX QUANTITY = 20

BENEFITS


Better dimming performance, flicker free during dimming.

ADVANTAGES

Dimming range (from 5% to 100%). Designed with global IC makers, brings an excellent dimming experience.

APPLICATIONS

Walkways, Hospital, Shops & Domestic.



GU5.3 - NON DIMMABLE (12V)



PART NO.	WATTAGE	REPLACEMENT WATTAGE	LUMENS	CCT (K)	CRI (Ra)	POWER FACTOR	BASE	MAX DIMENSIONS (mm)	
								Diameter	Length
DOM016	5W	35	345	3000	80	>0.4	GU5.3	50	45
DOM017	5W	35	360	4000	80	>0.4	GU5.3	50	45
DOM018	6W	50	430	3000	80	>0.4	GU5.3	50	45
DOM019	6W	50	430	4000	80	>0.4	GU5.3	50	45

BOX QUANTITY = 20

BENEFITS


Eco - Value. Broad transformer compatibility. Lower maintenance cost.

ADVANTAGES

Reliable IC solution. Excellent optical design.

APPLICATIONS

Walkways, Hospital, Shops & Domestic.





PAR 20 / PAR 30 TYPE - NON DIMMABLE (240V)



25,000
Hours



3
Years
Warranty



DOM032



DOM033

PART NO.	WATTAGE	REPLACEMENT WATTAGE	LUMENS	CCT (K)	CRI (Ra)	POWER FACTOR	BASE	MAX DIMENSIONS (mm)	
								Diameter	Length
DOM032	6.8W	50	500	3000	80	>0.5	E27	63	84
DOM033	12W	75	900	3000	80	>0.5	E27	95	90

BOX QUANTITY = 10

BENEFITS


- Perfect to replace traditional halogen PAR lamps
- Much less energy consumed than halogen PAR lamps for the same lumen output

ADVANTAGES

- A warm halogen natured accent beam, consistency in colour of light.

APPLICATIONS

- Shop, Hotel, Showcase, Museum & Exhibition halls.



AR111 TYPE - NON DIMMABLE (12V - 240V)



25,000
Hours



3
Years
Warranty



DOM034
DOM036



DOM035
DOM037



DOM034
DOM035



DOM036
DOM037




DOM034
DOM036



DOM035
DOM037

PART NO.	WATTAGE	REPLACEMENT WATTAGE	LUMENS	CCT (K)	CRI (Ra)	POWER FACTOR	BASE	MAX DIMENSIONS (mm)	
								Diameter	Length
DOM034	10.5W	100	910	4000	80	>0.5	GU10	111	56
DOM035	11W	100	850	4000	80	>0.5	G53	111	56
DOM036	10.5W	100	900	4000	80	>0.5	GU10	111	56
DOM037	11W	100	850	4000	80	>0.5	G53	111	56

BOX QUANTITY = 10



BENEFITS

- Professional accent lighting, perfect light quality.

ADVANTAGES

- Reliable solution, special LED chip package to improve heat dissipation.

APPLICATIONS

- Directional Light Source, Galleries, Museums, Exhibition Rooms & Retail.

R50 / R60 / R80 REFLECTOR TYPE - NON DIMMABLE (240V)

 25,000 Hours
 3 Years Warranty
 CE
 200-240V
 ErP
 A+ EEI
 BEAM ANGLE 110°



PART NO.	WATTAGE	REPLACEMENT WATTAGE	LUMENS	CCT (K)	CRI (Ra)	POWER FACTOR	BASE	MAX DIMENSIONS (mm)	
								Diameter	Length
DOM029	6W	35	430	2700	80	>0.5	E14	50	85
DOM030	9.5W	45	600	2700	80	>0.5	E27	63	103
DOM031	11W	60	820	4000	80	>0.5	E27	80	114

BOX QUANTITY = 10

BENEFITS


- Ideal replacement for traditional reflector lamps.
- Extra long lifetime, reduces frequency of lamp replacement.

ADVANTAGES

- Reliable IC solution for driver.
- User-friendly and eco-friendly, more than 25,000 hours life.

APPLICATIONS

- Shop, Hotel, Gallery, Museum, Domestic & Exhibition halls.



G4 / G9 TYPE - NON DIMMABLE (12V - 140V)

 25,000 Hours
 3 Years Warranty
 CE
 240V
 DC
 ErP
 A+ EEI
 BEAM ANGLE 100°
 BEAM ANGLE 145°



PART NO.	WATTAGE	REPLACEMENT WATTAGE	LUMENS	CCT (K)	CRI (Ra)	POWER FACTOR	BASE	MAX DIMENSIONS (mm)	
								Diameter	Length
DOM168	1W	10	80	2700	80	>0.4	G4	13.8	41
DOM169	1.5W	10	90	2700	80	>0.4	G9	13.8	46

BOX QUANTITY = 20

BENEFITS


- Perfect replacement for halogen G4 and G9 low energy consumption.
- Long life up to 25,000 hours.

ADVANTAGES

- Compact size.
- Excellent thermal solution.

APPLICATIONS

- Wall sconce, task lighting and decorative applications.





FROSTED GLS TYPE (A SERIES) - NON DIMMABLE (240V)



25,000
Hours



3
Years
Warranty



DOM050
TO
DOM053



DOM046
TO
DOM049



DOM038
TO
DOM045



DOM038
DOM040



DOM039
DOM041



DOM042
DOM044



DOM043
DOM045



DOM046
DOM048
DOM050
DOM052



DOM047
DOM049
DOM051
DOM053

PART NO.	WATTAGE	REPLACEMENT WATTAGE	LUMENS	CCT (K)	CRI (Ra)	POWER FACTOR	BASE	MAX DIMENSIONS (mm)	
								Diameter	Length
DOM038	5.6W	40	470	2700	80	>0.5	E27	60	110
DOM039	5.6W	40	470	2700	80	>0.5	B22	60	109
DOM040	5.6W	40	500	5000	80	>0.5	E27	60	110
DOM041	5.6W	40	500	5000	80	>0.5	B22	60	109
DOM042	9.2W	60	806	2700	80	>0.5	E27	60	110
DOM043	9.2W	60	806	2700	80	>0.5	B22	60	109
DOM044	9.2W	60	840	5000	80	>0.5	E27	60	110
DOM045	9.2W	60	840	5000	80	>0.5	B22	60	109
DOM046	11.6W	75	1060	2700	80	>0.5	E27	60	120
DOM047	11.6W	75	1060	2700	80	>0.5	B22	60	119
DOM048	11.6W	75	1150	5000	80	>0.5	E27	60	110
DOM049	11.6W	75	1150	5000	80	>0.5	B22	60	109
DOM050	12.5W	100	1521	2700	80	>0.5	E27	60	117
DOM051	12.5W	100	1521	2700	80	>0.5	B22	60	116
DOM052	12.5W	100	1600	5000	80	>0.5	E27	60	117
DOM053	12.5W	100	1600	5000	80	>0.5	B22	60	116

BENEFITS


- Even light distribution.
- Extra long lifetime, reduces the hassle of frequent replacements.

ADVANTAGES

- Wider beam angle in an ideal lamp shape.

APPLICATIONS

- General illumination, Indoor illumination.



BOX QUANTITY = 10

FROSTED GLS WITH DUSK TO DAWN SENSOR - NON DIMMABLE (240V)



25,000
Hours



3
Years
Warranty



DOM066
DOM068



DOM067
DOM069

PART NO.	WATTAGE	REPLACEMENT WATTAGE	LUMENS	CCT (K)	CRI (Ra)	POWER FACTOR	BASE	MAX DIMENSIONS (mm)	
								Diameter	Length
DOM066	6.6W	40	470	2700	80	>0.5	E27	60	109
DOM067	6.6W	40	470	2700	80	>0.5	B22	60	108
DOM068	6.6W	40	510	5000	80	>0.5	E27	60	109
DOM069	6.6W	40	510	5000	80	>0.5	B22	60	108

BENEFITS


- Dusk to Dawn Sensor, ideal for exterior and security lighting.

ADVANTAGES

- High lumen output.
- High lm/W.

APPLICATIONS

- General outdoor illumination.



BOX QUANTITY = 10

FROSTED GLS TYPE (A SERIES) - DIMMABLE (240V)



25,000
Hours



3
Years
Warranty



DOM062
TO
DOM065



DOM054
TO
DOM061



DOM054
DOM056



DOM055
DOM057



DOM058
DOM060



DOM059
DOM061



DOM062
DOM064



DOM063
DOM065

PART NO.	WATTAGE	REPLACEMENT WATTAGE	LUMENS	CCT (K)	CRI (Ra)	POWER FACTOR	BASE	MAX DIMENSIONS (mm)	
								Diameter	Length
DOM054	6.3W	40	470	2700	80	>0.9	E27	60	110
DOM055	6.3W	40	470	2700	80	>0.9	B22	60	109
DOM056	6.3W	40	500	5000	80	>0.9	E27	60	110
DOM057	6.3W	40	500	5000	80	>0.9	B22	60	109
DOM058	9W	60	806	2700	80	>0.9	E27	60	110
DOM059	9W	60	806	2700	80	>0.9	B22	60	109
DOM060	9W	60	860	5000	80	>0.9	E27	60	110
DOM061	9W	60	860	5000	80	>0.9	B22	60	109
DOM062	12W	75	1060	2700	80	>0.9	E27	60	120
DOM063	12W	75	1060	2700	80	>0.9	B22	60	120
DOM064	12W	75	1150	5000	80	>0.9	E27	60	122
DOM065	12W	75	1150	5000	80	>0.9	B22	60	122

BOX QUANTITY = 10

BENEFITS


- Tested with major dimmers.
- Better dimming performance, flicker free.

ADVANTAGES

- Designed with global IC makers, excellent dimming quality.

APPLICATIONS

- General illumination, Indoor illumination.



PYGMY TYPE - NON DIMMABLE (240V)



25,000
Hours



3
Years
Warranty



DOM166



DOM167

PART NO.	WATTAGE	REPLACEMENT WATTAGE	LUMENS	CCT (K)	CRI (Ra)	POWER FACTOR	BASE	MAX DIMENSIONS (mm)	
								Diameter	Length
DOM166	1.6W	12W	110	2700	80	>0.9	E14	58	100
DOM167	1.6W	12W	110	2700	80	>0.9	E14	58	100

BOX QUANTITY = 20

BENEFITS


- Integrated light source, gentle and soft light.

ADVANTAGES

- Streamlined appearance design.

APPLICATIONS

- Refrigerator, Mirror lamp.



CLEAR CANDLE TYPE - NON DIMMABLE (240V)



25,000 Hours



3 Years Warranty



DOM110 TO DOM117



DOM102 TO DOM109



PART NO.	WATTAGE	REPLACEMENT WATTAGE	LUMENS	CCT (K)	CRI (Ra)	POWER FACTOR	BASE	MAX DIMENSIONS (mm)	
								Diameter	Length
DOM102	3.4W	25	250	2700	80	>0.4	E27	35	98
DOM103	3.4W	25	250	2700	80	>0.4	B22	35	98
DOM104	3.4W	25	250	2700	80	>0.4	E14	35	102
DOM105	3.4W	25	250	2700	80	>0.4	B15	35	101
DOM106	3.4W	25	260	5000	80	>0.4	E27	35	98
DOM107	3.4W	25	260	5000	80	>0.4	B22	35	98
DOM108	3.4W	25	260	5000	80	>0.4	E14	35	102
DOM109	3.4W	25	260	5000	80	>0.4	B15	35	101
DOM110	5.9W	40	470	2700	80	>0.5	E27	35	98
DOM111	5.9W	40	470	2700	80	>0.5	B22	38	109
DOM112	5.9W	40	470	2700	80	>0.5	E14	38	108
DOM113	5.9W	40	470	2700	80	>0.5	B15	38	110
DOM114	5.9W	40	490	5000	80	>0.5	E27	38	108
DOM115	5.9W	40	480	5000	80	>0.5	B22	35	98
DOM116	5.9W	40	480	5000	80	>0.5	E14	38	110
DOM117	5.9W	40	480	5000	80	>0.5	B15	38	108

BOX QUANTITY = 10

CLEAR CANDLE TYPE - DIMMABLE (240V)



25,000 Hours



3 Years Warranty



(ADDITIONAL TYPES ON NEXT PAGE)

PART NO.	WATTAGE	REPLACEMENT WATTAGE	LUMENS	CCT (K)	CRI (Ra)	POWER FACTOR	BASE	MAX DIMENSIONS (mm)	
								Diameter	Length
DOM118	3.5W	25	250	2700	80	>0.5	E27	38	108
DOM119	3.5W	25	250	2700	80	>0.5	B22	38	108
DOM122	3.5W	25	270	5000	80	>0.5	E27	38	108
DOM123	3.5W	25	270	5000	80	>0.5	B22	38	108

BOX QUANTITY = 10

BENEFITS


- Up to 80% energy saving.
- High efficiency.
- Reliable quality.
- New IC driver and heatsink design.

ADVANTAGES

- New heat dissipation design with smaller size.

APPLICATIONS

- Desk lamp, Crystal chandelier, Bedrooms, Restaurants, Domestic & Hotels.



BENEFITS


- Suitable for most dimmers, creates a warm ambience.
- High performance dimming, enjoy smooth, flicker free dimming effect.
- Consistent light.

ADVANTAGES

- Excellent dimmer match.
- IC driver design.

APPLICATIONS

- Desk lamp, Crystal chandelier, Bedrooms, Restaurants, Domestic & Hotels.





CLEAR CANDLE TYPE - DIMMABLE (240V)



25,000 Hours



3 Years Warranty



DOM120
DOM124



DOM121
DOM125



DOM126
DOM130



DOM127
DOM131



DOM128
DOM132



DOM129
DOM133

BENEFITS


- Suitable for most dimmers, creates a warm ambience.
- High performance dimming, enjoy smooth, flicker free dimming effect.
- Consistent light.

ADVANTAGES

- Excellent dimmer match.
- IC driver design.

APPLICATIONS

- Desk lamp, Crystal chandelier, Bedrooms, Restaurants, Domestic & Hotels.



PART NO.	WATTAGE	REPLACEMENT WATTAGE	LUMENS	CCT (K)	CRI (Ra)	POWER FACTOR	BASE	MAX DIMENSIONS (mm)	
								Diameter	Length
DOM120	3.5W	25	250	2700	80	>0.5	E14	38	110
DOM121	3.5W	25	250	2700	80	>0.5	B15	38	108
DOM124	3.5W	25	270	5000	80	>0.5	E14	38	110
DOM125	3.5W	25	270	5000	80	>0.5	B15	38	108
DOM126	6W	40	470	2700	80	>0.9	E27	38	109
DOM127	6W	40	470	2700	80	>0.9	B22	38	108
DOM128	6W	40	470	2700	80	>0.9	E14	38	110
DOM129	6W	40	470	2700	80	>0.9	B15	38	108
DOM130	6W	40	500	5000	80	>0.9	E27	38	109
DOM131	6W	40	500	5000	80	>0.9	B22	38	108
DOM132	6W	40	500	5000	80	>0.9	E14	38	110
DOM133	6W	40	500	5000	80	>0.9	B15	38	108

BOX QUANTITY = 10

FROSTED CANDLE TYPE - NON DIMMABLE (240V)



25,000 Hours



3 Years Warranty



DOM070
DOM074



DOM071
DOM075



DOM072
DOM076



DOM073
DOM077



DOM078
DOM082



DOM079
DOM083



DOM080
DOM084



DOM081
DOM085

BENEFITS


- Up to 80% energy savings.
- Reliable quality.
- New IC driver and heatsink design.

ADVANTAGES

- New heat dissipation design with smaller size.

APPLICATIONS

- Desk lamp, Crystal chandelier, Bedrooms & Restaurants.



PART NO.	WATTAGE	REPLACEMENT WATTAGE	LUMENS	CCT (K)	CRI (Ra)	POWER FACTOR	BASE	MAX DIMENSIONS (mm)	
								Diameter	Length
DOM070	3.4W	25	250	2700	80	>0.4	E27	35	98
DOM071	3.4W	25	250	2700	80	>0.4	B22	35	97
DOM072	3.4W	25	250	2700	80	>0.4	E14	35	102
DOM073	3.4W	25	250	2700	80	>0.4	B15	35	101
DOM074	3.4W	25	270	5000	80	>0.4	E27	35	98
DOM075	3.4W	25	270	5000	80	>0.4	B22	35	97
DOM076	3.4W	25	270	5000	80	>0.4	E14	35	98
DOM077	3.4W	25	270	5000	80	>0.4	B15	35	101
DOM078	5.9W	40	470	2700	80	>0.5	E27	35	98
DOM079	5.9W	40	470	2700	80	>0.5	B22	35	98
DOM080	5.9W	40	470	2700	80	>0.5	E14	35	105
DOM081	5.9W	40	470	2700	80	>0.5	B15	38	108
DOM082	5.9W	40	490	5000	80	>0.5	E27	35	98
DOM083	5.9W	40	490	5000	80	>0.5	B22	35	98
DOM084	5.9W	40	490	5000	80	>0.5	E14	35	105
DOM085	5.9W	40	490	5000	80	>0.5	B15	38	108

BOX QUANTITY = 10

FROSTED CANDLE TYPE - DIMMABLE (240V)



25,000
Hours



3
Years
Warranty



200-240V



BEAM
ANGLE
260°
DOM086
TO
DOM089



BEAM
ANGLE
280°
DOM090
TO
DOM093



DIMMABLE



DOM086
DOM090



DOM087
DOM091



DOM088
DOM092



DOM089
DOM093



DOM094
DOM098



DOM095
DOM099



DOM096
DOM100



DOM097
DOM101

PART NO.	WATTAGE	REPLACEMENT WATTAGE	LUMENS	CCT (K)	CRI (Ra)	POWER FACTOR	BASE	MAX DIMENSIONS (mm)	
								Diameter	Length
DOM086	3.5W	25	250	2700	80	>0.5	E27	38	108
DOM087	3.5W	25	250	2700	80	>0.5	B22	38	108
DOM088	3.5W	25	250	2700	80	>0.5	E14	38	110
DOM089	3.5W	25	250	2700	80	>0.5	B15	38	108
DOM090	3.5W	25	270	5000	80	>0.5	E27	38	108
DOM091	3.5W	25	270	5000	80	>0.5	B22	38	108
DOM092	3.5W	25	270	5000	80	>0.5	E14	38	102
DOM093	3.5W	25	270	5000	80	>0.5	B15	38	109
DOM094	6W	40	470	2700	80	>0.9	E27	38	102
DOM095	6W	40	470	2700	80	>0.9	B22	38	110
DOM096	6W	40	470	2700	80	>0.9	E14	38	108
DOM097	6W	40	470	2700	80	>0.9	B15	38	108
DOM098	6W	40	500	5000	80	>0.9	E27	38	108
DOM099	6W	40	500	5000	80	>0.9	B22	38	108
DOM100	6W	40	500	5000	80	>0.9	E14	38	110
DOM101	6W	40	500	5000	80	>0.9	B15	38	108

BENEFITS


- Suitable for most dimmers, creates a warm ambience.
- High performance dimming, enjoy smooth, flicker free dimming effect.
- Consistent light.

ADVANTAGES

- Excellent dimmer match.
- IC driver design.

APPLICATIONS

- Desk lamp, Crystal chandelier, Bedrooms, Restaurants, Domestic & Hotels.



BOX QUANTITY = 10



CLEAR GOLF BALL TYPE - NON DIMMABLE (240V)



25,000 Hours



3 Years Warranty



DOM150 DOM194 DOM151 DOM152 DOM156 DOM196 DOM158 DOM157
DOM153 DOM195 DOM155 DOM154 DOM159 DOM197 DOM161 DOM160

PART NO.	WATTAGE	REPLACEMENT WATTAGE	LUMENS	CCT (K)	CRI (Ra)	POWER FACTOR	BASE	MAX DIMENSIONS (mm)	
								Diameter	Length
DOM150	3.4W	25	250	2700	80	>0.4	E27	45	74
DOM151	3.4W	25	250	2700	80	>0.4	E14	45	78
DOM152	3.4W	25	250	2700	80	>0.4	B15	45	77
DOM153	3.4W	25	280	5000	80	>0.4	E27	45	74
DOM154	3.4W	25	270	5000	80	>0.4	B15	45	77
DOM155	3.4W	25	270	5000	80	>0.4	E14	45	78
DOM156	5.9W	40	470	2700	80	>0.5	E27	45	74
DOM157	5.9W	40	470	2700	80	>0.5	B15	45	80
DOM158	5.9W	40	470	2700	80	>0.5	E14	45	81
DOM159	5.9W	40	490	5000	80	>0.5	E27	45	78
DOM160	5.9W	40	490	5000	80	>0.5	B15	45	80
DOM161	5.9W	40	490	5000	80	>0.5	E14	45	81
DOM194	3.4W	25	250	2700	80	>0.4	B22	45	73
DOM195	3.4W	25	270	5000	80	>0.4	B22	45	73
DOM196	5.9W	40	470	2700	80	>0.5	B22	45	77
DOM197	5.9W	40	490	5000	80	>0.5	B22	45	73

BOX QUANTITY = 10

CLEAR GOLF BALL TYPE - DIMMABLE (240V)



25,000 Hours



3 Years Warranty



DOM164
DOM165



DOM162
DOM163



DOM162 DOM164
DOM163 DOM165

PART NO.	WATTAGE	REPLACEMENT WATTAGE	LUMENS	CCT (K)	CRI (Ra)	POWER FACTOR	BASE	MAX DIMENSIONS (mm)	
								Diameter	Length
DOM162	3.5W	25	250	2700	80	>0.5	E14	45	81
DOM163	3.5W	25	270	5000	80	>0.5	E14	45	81
DOM164	6W	40	470	2700	80	>0.9	E14	45	81
DOM165	6W	40	500	5000	80	>0.9	E14	45	81

BOX QUANTITY = 10

BENEFITS


- Up to 80% energy saving.
- High efficiency.
- Reliable quality.
- New IC driver and heatsink design.

ADVANTAGES

- New heat dissipation design with smaller size.

APPLICATIONS

- Desk lamp, Bedrooms, Restaurants, Domestic & Hotels.



BENEFITS


- Suitable for most dimmers, creates a warm ambience.
- High performance dimming, enjoy smooth, flicker free dimming.
- Stable light quality.

ADVANTAGES

- Excellent dimmer match.
- IC driver design.

APPLICATIONS

- Chandelier, Bedrooms, Restaurants, Domestic & Hotels.





FROSTED GOLF BALL TYPE - NON DIMMABLE (240V)



25,000
Hours



3
Years
Warranty



DOM192
TO
DOM145



DOM134
TO
DOM191



DOM134
DOM137



DOM190
DOM191



DOM135
DOM138



DOM136
DOM139



DOM140
DOM143



DOM192
DOM193



DOM141
DOM144



DOM142
DOM145

PART NO.	WATTAGE	REPLACEMENT WATTAGE	LUMENS	CCT (K)	CRI (Ra)	POWER FACTOR	BASE	MAX DIMENSIONS (mm)	
								Diameter	Length
DOM134	3.4W	25	250	2700	80	>0.4	E27	45	74
DOM135	3.4W	25	250	2700	80	>0.4	E14	45	78
DOM136	3.4W	25	250	2700	80	>0.4	B15	45	77
DOM137	3.4W	25	280	5000	80	>0.4	E27	45	74
DOM138	3.4W	25	280	5000	80	>0.4	E14	45	77
DOM139	3.4W	25	280	5000	80	>0.4	B15	45	78
DOM190	3.4W	25	250	2700	80	>0.4	B22	45	73
DOM191	3.4W	25	280	5000	80	>0.4	B22	45	77
DOM192	5.9W	40	470	2700	80	>0.5	B22	45	77
DOM193	5.9W	40	490	5000	80	>0.5	B22	45	77
DOM140	5.9W	40	470	2700	80	>0.5	E27	45	74
DOM141	5.9W	40	470	2700	80	>0.5	E14	45	78
DOM142	5.9W	40	470	2700	80	>0.5	B15	45	79
DOM143	5.9W	40	490	5000	80	>0.5	E27	45	74
DOM144	5.9W	40	490	5000	80	>0.5	E14	45	78
DOM145	5.9W	40	490	5000	80	>0.5	B15	45	81

BOX QUANTITY = 10

FROSTED GOLF BALL TYPE - DIMMABLE (240V)



25,000
Hours



3
Years
Warranty



DOM146
DOM147



DOM148
DOM149

PART NO.	WATTAGE	REPLACEMENT WATTAGE	LUMENS	CCT (K)	CRI (Ra)	POWER FACTOR	BASE	MAX DIMENSIONS (mm)	
								Diameter	Length
DOM146	3.6W	25	250	2700	80	>0.5	E14	45	81
DOM147	3.5W	25	270	5000	80	>0.5	E14	45	81
DOM148	6W	40	470	2700	80	>0.9	E14	45	81
DOM149	6W	40	500	5000	80	>0.9	E14	45	81

BOX QUANTITY = 10

BENEFITS


- Up to 80% energy saving.
- High efficiency.
- Reliable quality.
- New IC driver and heatsink design.

ADVANTAGES

- New heat dissipation design with smaller size.

APPLICATIONS

- Desk lamp, Bedrooms, Restaurants, Domestic & Hotels.



BENEFITS

- Suitable for most dimmers, creates a warm ambience.
- High performance dimming, enjoy smooth, flicker free dimming.
- Stable light quality.

ADVANTAGES

- Excellent dimmer match.
- IC driver design.

APPLICATIONS

- Chandelier, Bedrooms, Restaurants, Domestic & Hotels.

